



Vierkantrohre gepresst
Tubes carrés pressés

EN AW-6060
AlMgSi (AlMgSi0.5)

Chem. Zusammensetzung: DIN EN 573-3
Composition chimique:
Mech. Wert/Prop. mécaniques: DIN EN 755-2
Dimension/Dimension: DIN EN 755-9
Stangenlänge/Longueur: 6 m
Zustand/Etat: T66, nach/selon DIN EN 515

mm					kg/m	EN AW-6060
15	x	15	x	1	0.15	●
15	x	15	x	1.5	0.22	●
15	x	15	x	2	0.28	●
20	x	20	x	1.5	0.30	●
20	x	20	x	2	0.39	●
20	x	20	x	3	0.55	●
25	x	25	x	1.5	0.38	●
25	x	25	x	2	0.50	●
25	x	25	x	3	0.71	●
30	x	30	x	2	0.60	●
30	x	30	x	3	0.87	●
34	x	34	x	2	0.69	●
34	x	34	x	3	1.00	●
35	x	35	x	2	0.71	●
35	x	35	x	3	1.04	●
40	x	40	x	2	0.82	●
40	x	40	x	2.5	1.01	●
40	x	40	x	3	1.20	●
40	x	40	x	4	1.56	●
45	x	45	x	2	0.93	●
50	x	50	x	2	1.04	●
50	x	50	x	2.5	1.28	●
50	x	50	x	3	1.52	●
50	x	50	x	4	1.99	●
50	x	50	x	5	2.43	●
60	x	60	x	2	1.25	●
60	x	60	x	3	1.85	●
60	x	60	x	4	2.42	●
70	x	70	x	2	1.47	●

mm					kg/m	EN AW-6060
70	x	70	x	4	2.85	●
80	x	80	x	2	1.68	●
80	x	80	x	3	2.49	●
80	x	80	x	4	3.28	●
80	x	80	x	5	4.05	●
80	x	80	x	6	4.80	●
100	x	100	x	2	2.12	●
100	x	100	x	3	3.14	●
100	x	100	x	4	4.15	●
100	x	100	x	5	5.13	●