



Bleche/Platten gewalzt
Tôles/plaques laminées

EN AW-6082
AlSi1MgMn (AlMgSi1)

Verfahren bis 5 mm kaltgewalzt, ab 6 mm warmgewalzt
 Procédé: jusqu'à 5 mm laminé à froid, dès 6 mm laminé à chaud
 Chem. Zusammensetzung DIN EN 573-3
 Composition chimique:
 Mech.Wert/Propr. mécaniques: DIN EN 485-2
 Dimension/Dimension: DIN EN 485-3/4
 Zustand/Etat: bis/jusqu'à 5.0 mm T6, ab/dès 6.0 mm T651, nach/selon DIN EN 515

mm				kg/Tafel	EN AW-6082	
				kg/tôle		
2020	x	1020	x	1.0	5.56	●
2020	x	1020	x	1.5	8.34	●
2020	x	1020	x	2.0	11.13	●
2020	x	1020	x	2.5	13.91	●
2020	x	1020	x	3.0	16.69	●
3020	x	1520	x	4.0	49.58	●
2520	x	1270	x	5.0	43.21	●
2520	x	1270	x	6.0	51.85	●
3020	x	1520	x	8.0	99.15	●
3020	x	1520	x	10.0	123.94	●
3020	x	1520	x	12.0	148.73	●
3020	x	1520	x	15.0	185.91	●
3020	x	1520	x	20.0	247.88	●
3020	x	1520	x	25.0	309.85	●
3020	x	1520	x	30.0	371.82	●
3020	x	1520	x	35.0	433.79	●
3020	x	1520	x	40.0	495.76	●
3020	x	1520	x	45.0	557.73	●
3020	x	1520	x	50.0	619.70	●
3020	x	1520	x	60.0	743.64	●
3020	x	1520	x	70.0	867.59	●
3020	x	1520	x	80.0	991.53	●
2520	x	1270	x	100.0	864.11	●
2520	x	1270	x	110.0	950.52	●
2520	x	1270	x	120.0	1036.93	●
2020	x	1020	x	130.0	723.20	●
2020	x	1020	x	140.0	778.83	●
2020	x	1020	x	150.0	834.46	●