



Winkelprofile gepresst
Equerres pressées

CW614N
CW620N
CW623N

CuZn39Pb3
CuZn41Pb1Al
CuZn43Pb2

Norm/Norme: DIN EN 12167
Zustand gepresst, ohne vorgeschriebene Festigkeitswerte
Etat: pressé, caractéristiques mécaniques non définies
Stangenlänge/Longueur: 5 m

mm					kg/m	CuZn39Pb3 CuZn41Pb1Al CuZn43Pb2
10	x	10	x	2	0.31	●
12	x	12	x	2	0.37	●
15	x	10	x	2	0.39	●
15	x	15	x	2	0.48	●
15	x	15	x	3	0.69	●
20	x	10	x	2	0.48	●
20	x	20	x	2	0.65	●
20	x	20	x	3	0.94	●
25	x	10	x	2	0.56	●
25	x	25	x	2	0.82	●
25	x	25	x	3	1.20	●
25	x	25	x	4	1.56	●
30	x	20	x	2	0.82	●
30	x	20	x	3	1.20	●
30	x	30	x	2	0.99	●
30	x	30	x	3	1.45	●
30	x	30	x	4	1.90	●
30	x	30	x	5	2.34	●
40	x	40	x	3	1.96	●
40	x	40	x	4	2.58	●
50	x	20	x	3	1.71	●
50	x	50	x	4	3.26	●
50	x	50	x	5	4.04	●
60	x	60	x	4	3.94	●